

24mm Metal Shaft Rotary Potentiometer

Electrical Characteristics

All Resistance	1K ~ 1MΩ				
All Resistance Tolerance	± 20% (more than 1MΩ ± 30%)				
Resistance Taper	A. B. C. D. W. Taper				
Resistance Taper Characteristics	A50%	B50%	C50%	D50%	W50%
	15-25%	40-60%	75-85%	2-15%	45-55%
Rated Power	B Taper: AC500V0.5W; Other Taper: AC250V0.25 W				
Residual Resistance	$R \geq 250K\Omega$ 0.1% $250K\Omega > R > 10K\Omega$ 10Ω Max. $10K\Omega \geq R$ 10Ω Max.				
Noise	47 mV max.				
Insulation Resistance	More than 100MΩ at DC 500V				
Withstand Voltage	1 minute at AC 250V				
Rotational Life	15,000 Cycles.				

Mechanical Characteristics

Total Rotational Angle	300° ± 10°
Stopper Strength	5 kgf.cm max./ 3 sec .
Rotational Torque	30 ~ 200gf.cm max.
Push-Pull Strength	10 kgf.cm max./3 sec.
Solder Heat	300°C,3s (Only For Hand-Soldering)
Remark	Shaft: Cast Iron , Aluminum Zinc , Plastic Bushing Material: cast iron