


PCB MOUNTING HOLES  
(VIEWED FROM COPPER SIDE)



CIRCUIT DIAGRAM

NO.	PART NAME	Q'TY	MATERIAL (THICKNESS, COLOR)	REMARK
10	SEPARATOR	2	POM	RoHS COMPLIANT
9	MAKE TERMINAL (1a, 5e)	2	QSn6.5-0.1Y t=0.3 (C5210R-H)	Ag-PLATED; RoHS COMPLIANT
8	WASHER	1	ABS 94HB	RoHS COMPLIANT
7	TIP TERMINAL (4d)	1	QSn6.5-0.1Y t=0.4 (C5210R-H)	Ag-PLATED RoHS COMPLIANT
6	BREAK TERMINAL (3c, 7g)	2	H62Y t=0.4 (C2680R-H)	
5	TRANSFER TERMINAL (2b, 6f)	2	QSn6.5-0.1Y t=0.35 (C5210R-H)	
4	RING TERMINAL (8h)	1	QSn6.5-0.1Y t=0.3 (C5210R-H)	
3	EARTH TERMINAL (9i)	1	t=0.6 Fe (STEEL)	CuSn-PLATED; RoHS COMPLIANT
2	HOUSING	1	PBT G10	RoHS COMPLIANT
1	SCREW	1	H59 (COPPER ALLOY)	Ni-PLATED; RoHS COMPLIANT

Dimensions unless otherwise specified

Size Range	Tolerance
$L \leq 1$	$\pm 0.15$
$1 < L \leq 8$	$\pm 0.20$
$8 < L \leq 23$	$\pm 0.25$
$23 < L \leq 50$	$\pm 0.30$
ANGAL	$\pm 1^\circ$



SCALE: 3:2  
VIEW:   
UNIT: mm

NAME: PHONE JACK  
CAT. NO. SCJ-0625HA