



800-227-0075

<http://www.vimex.com>

Part Number System

T 8 0 1 9 L - S - E - Q - E - S - T 1 - 2

Switch Function (SPDT)				Actuator		Bushing		Contact	Epoxy Seal	Support Bracket Type		Actuator Cap		Cap Color	
Model No.	Switching Position														
				S	10.41	E	(STD)	8.89	Q	(none)	(none)	T1	10.29 actuator S	0	Clear
T8019L	ON	none	ON	T	5.08	M	non-thrd	8.89	R	E	S	T2	7.28 actuator T	1	White
T8019LA	ON	none	(ON)	X	13.97	K	metric	8.89	G					2	Black
T8020L	ON	OFF	ON	W	21.34	F		7.10	K					3	Red
T8020LA	(ON)	OFF	(ON)	V	16.26	N	non-thrd	7.10						4	Yellow
T8020LB	ON	OFF	(ON)	Flatted Toggle		G		7.52						5	Blue
Term Comm	2-3	open	2-1	U	11.43	G1	non-thrd	7.52						6	Green
				U1	7.20	H		8.00						7	Orange
				Locking Lever		H1	non-thrd	8.00							
				LK	Round	J	(long)	9.60							
				LK1	Flat top	J1	non-thrd	9.60							
						L	splash-prf	7.47							
						none									
						No code if LK/LK1 actuator unless splash proof or non-thread chosen									

See following pages for details

				Description:	Build a part number.
Page:	1	Date:	2003-12-17	P/N	T8019L
of:	5	Revision:	1.0		



800-227-0075

<http://www.vimex.com>

Part Number System

Actuator Options				
S (standard)	T (standard)	X (long)	W (long)	V (long)
Flatted Actuators (only available with 'H' or 'H1' or 'H2' bushing)			Locking Lever	
U (standard)	U1 (short)		LK (round top)	LK1 (flat top)
Bushing option code not required unless 'L' splashproof bushing is ordered			Bushing option code not required unless: (1) 'L' splashproof bushing ordered (i.e. LKL or LK1L) (2) non-thread bushing required choose bushing code 'N' (i.e. LKN or LK1N) Locking Levers ONLY available with ON-ON or ON-OFF-ON action.	

				Description:	Build a part number.
Page:	2	Date:	2003-12-17	P/N	T8019L
of:	5	Revision:	1.0		



800-227-0075

<http://www.vimex.com>

Part Number System

Bushing Option					
E threaded (standard) M non-thread	F threaded N non-thread	G threaded (standard) G1 non-thread	H threaded (standard) H1 non-thread H2 Metric	J threaded (standard) J1 non-thread	K Metric

Splash proof Solution			
L			

				Description:	Build a part number.
Page:	3	Date:	2003-12-17	P/N	T8019L
of:	5	Revision:	1.0		



800-227-0075

<http://www.vimex.com>

Part Number System

Panel Mounting

1/4" Bushing			Metric Bushing	
keyway	flatted D	with locking ring	keyway	with locking ring

Contact Material Options

Code	Contact Material	Terminal Material	Rating
Q	Silver plated	Silver plated	5A @ 120VAC or 28VDC; 2A @ 250VAC
R	Gold plated over nickel plated	Gold plated over nickel plated	0.4VA max. @ 20VAC or VDC max.
G	Gold plated over silver plated	Gold plated over silver plated	0.4VA max. @ 20VAC or VDC max. or 5A @ 120VAC or 28VDC; 2A @ 250VAC
K	Gold plated over nickel plated	Tin-lead over nickel plated	0.4VA max. @ 20VAC or VDC max.



				Description:	Build a part number.
Page:	4	Date:	2003-12-17	P/N	T8019L
of:	5	Revision:	1.0		











800-227-0075

<http://www.vimex.com>

Part Number System

Toggle Cap Option		Toggle Cap Color Option	
T1 (for 'S' actuator only)	T2 (for 'T' actuator only)	Code	Color
 .405 10.29 Material Vinyl	 .287 7.29 Material Vinyl	0	Transparent
		1	White
		2	Black
		3	Red
		4	Yellow
		5	Blue
		6	Green
		7	Orange

Hardware					
1/4-40NS hex (standard)	1/4-40NS DRESS NUT	Metric hex	1/4" & M6 Lock Ring	Flatted bush Lock Ring	1/4" & M6 Lock Washer
 .312 7.92 1/4-40NS  .062 1.57	 .352 8.94 1/4-40UNS  .372 DIA 9.45ø .118 3.00	 .409 10.39 M6P 0.75 THD. .354 8.99  .062 1.57	 .468 DIA ø11.89 .029 0.74 .065 1.65	 .468 DIA ø11.89 .029 0.74 .065 1.65	 .408 DIA ø10.36 .018 0.46 THK

				Description:	Build a part number.
Page:	5	Date:	2003-12-17	P/N	T8019L
of:	5	Revision:	1.0		